

Specification Models	PSGP-1015AHR	PSGP-1020AHR	PSGP-1025AHR	PSGP-1030AHR	PSGP-1040AHR	PSGP-1050AHR	PSGP-1060AHR	PSGP-1220AHR	PSGP-1225AHR	PSGP-1230AHR	PSGP-1240AHR	PSGP-1250AHR	PSGP-1260AHR	PSGP-1522AHR	PSGP-1530AHR	PSGP-1540AHR	PSGP-1550AHR	PSGP-1560AHR	
テーブル最大移動量(前後・左右)	1200×1650mm	1200×2150mm	1200×2650mm	1200×3150mm	1200×4150mm	1200×5150mm	1200×6150mm	1400×2150mm	1400×2650mm	1400×3150mm	1400×4150mm	1400×5150mm	1400×6150mm	1900×2350mm	1900×3150mm	1900×4150mm	1900×5150mm	1900×6150mm	
立軸砥石下面よりチャック取付面迄の距離	0.750mm													100-800(350-1000)mm					
横軸砥石軸中心よりチャック取付面迄の距離	≒1100mm													approx.1100(1350)mm					
研削可能寸法(巾×長)	1000×1500mm	1000×2000mm	1000×2500mm	1000×3000mm	1000×4000mm	1000×5000mm	1000×6000mm	1200×2000mm	1200×2500mm	1200×3000mm	1200×4000mm	1200×5000mm	1200×6000mm	1500×2200mm	1500×3000mm	1500×4000mm	1500×5000mm	1500×6000mm	
テーブルスピード(油圧60Hz)	2-25-(1-25)m/min																		
油圧モーター出力	7.5kW/10HP				11kW/15HP					11kW/15HP			15kW/20HP		9.3kW/12.5HP	13kW/17.5HP	15kW/20HP	18.6kW/25HP	22.5kW/30HP
門内巾	1200mm							1400mm					1900mm						
クロスステップ送り量	0.1-35mm/feed																		
クロス連続送り量	3m/min																		
クロスハンド毎1回転当たりの移動量	10mm																		
クロスハンド毎1目盛当たりの移動量	0.05mm																		
横軸上下早送りスピード	240mm/mn																		
上下ハンド毎1回転当たりの切込量	0.25mm																		
上下ハンド毎1目盛当たりの切込量	0.002mm																		
横軸砥石寸法(外径×巾×内径)	500×100×203.2mm																		
立軸砥石寸法(外径×巾×内径)	335×50×127																		
横軸駆動モーター	11(15,18.5)kW/15(20,25)HP																		
立軸駆動モーター	7.5kW/10HP																		
砥石回転数	1150r.p.m.																		
	13000Kg	17000Kg	21500Kg	26500Kg	41000Kg	45000Kg	49500Kg	18000Kg	22500Kg	27500Kg	41000Kg	46000Kg	51500Kg	37000Kg	43000Kg	49500Kg	55000Kg	62000Kg	
	5.1×2.9×3.4m	6.2×2.9×3.4m	7.3×2.9×3.4m	8.4×2.9×3.4m	11.2×2.9×3.5m	13.4×2.9×3.5m	15.6×2.9×3.5m	6.2×2.9×3.4m	7.3×2.9×3.4m	8.4×2.9×3.4m	11.2×2.9×3.5m	13.4×2.9×3.5	15.6×2.9×3.5m	6.6×3.5×3.8m	8.4×3.5×3.8m	11.2×3.5×3.8m	13.4×3.5×3.8m	15.6×3.5×3.8m	

